



US009881277B2

(12) **United States Patent**  
**Brady**

(10) **Patent No.:** **US 9,881,277 B2**  
(45) **Date of Patent:** **Jan. 30, 2018**

(54) **WRIST BAND HAPTIC FEEDBACK SYSTEM**

(71) Applicant: **Amazon Technologies, Inc.**, Seattle,  
WA (US)

(72) Inventor: **Tye Michael Brady**, Southborough,  
MA (US)

(73) Assignee: **Amazon Technologies, Inc.**, Seattle,  
WA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/083,107**

(22) Filed: **Mar. 28, 2016**

(65) **Prior Publication Data**

US 2017/0278052 A1 Sep. 28, 2017

(51) **Int. Cl.**  
**G06K 7/10** (2006.01)  
**G06Q 10/08** (2012.01)

(52) **U.S. Cl.**  
CPC ..... **G06Q 10/087** (2013.01); **G06K 7/10891**  
(2013.01)

(58) **Field of Classification Search**  
USPC ..... 235/385, 492, 487; 705/7.29, 28  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,504,949 B1 3/2009 Rouaix et al.  
7,911,324 B2 \* 3/2011 Breed ..... G01S 13/878  
307/10.1  
8,280,547 B2 10/2012 D'Andrea et al.

9,087,314 B2 7/2015 Hoffman et al.  
9,242,799 B1 1/2016 O'Brien et al.  
2007/0063895 A1 \* 3/2007 August ..... G06K 7/0008  
342/359  
2007/0156312 A1 \* 7/2007 Breed ..... B60C 23/007  
701/31.4  
2009/0207694 A1 8/2009 Guigne et al.  
(Continued)

#### OTHER PUBLICATIONS

U.S. Appl. No. 15/083,083, filed Mar. 28, 2016, Titled: Ultrasonic  
Bracelet and Receiver for Detecting Position in 2D Plane.  
(Continued)

*Primary Examiner* — Allyson Trail

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend &  
Stockton LLP

(57) **ABSTRACT**

Inventory management systems and related methods employ radio frequency based tracking of a worker's hands to monitor performance of inventory tasks. An inventory management system includes inventory bins, a user-wearable unit configured to be worn in proximity to a user's hand, fixed RF antennas configured to transmit at least one RF interrogation signal and receive at least one RF response signal, a RF transceiver operatively coupled with the fixed RF antennas, and a management module operatively coupled with the RF transceiver. The user-wearable unit includes an RF transceiver configured to transmit RF response signals in response to reception of the at least one RF interrogation signal. The management module is configured to process signals generated by the RF transceiver to track locations of the user-wearable unit and identify an inventory bin based on proximity of the user-wearable unit to the identified inventory bin to monitor performance of an inventory system task.

**20 Claims, 17 Drawing Sheets**

